

The IntelliDOCK 9555 is the ideal low cost accessory for using the Iridium 9555 handset for various maritime, transport or fixed site applications.

The purpose built cradle simply docks the 9555 handset securely, providing an integrated antenna, data and power connection that makes it possible to keep all antenna cables and power permanently connected to the dock ready for use. The 9555 handset is easily inserted and removed by the press of a button on the top of the dock making it very easy to remove the 9555 for use out of the dock at anytime.

IntelliDOCK 9555 also supports the use of an optional compact Beam Privacy Handset (RST755) that can be located next to the IntelliDOCK 9555 for added convenience if required.

#### **APPLICATIONS**



Boating



4WD



Transport



In-building

### **KEY FEATURES**

#### INTELLIDOCK CRADLE

- Securely holds 9555 handset
- Robust design and construction
- Charges 9555 handset ready for use
- Integrated antenna connection
- Handset always charged ready for use

#### **INTEGRATED BLUETOOTH®**

- Bluetooth® in-built in cradle
- Supports Bluetooth® Voice & Data Accessories
- Convenient hands-free calling

#### **IN-BUILT RINGER**

• In-built ringer for enhanced ring indication

#### VOICE, DATA, SMS, SBD

- Supports all Iridium voice, data, SMS and SBD services
- Access to prepaid, post paid & crew calling
- Bluetooth® & USB data connectivity

#### **PRIVACY HANDSET**

- Supports optional Beam privacy handset
- Auto sensing answer/hang-up intelligence

#### INSTALLATION

- Supports 9 32V DC power input
- Flexible installation via universal mount, also suitable for wall mounting
- Optional 110 240V AC plug pack available

#### QUALITY

- Professional industrial design
- 2 years peace of mind, replacement guarantee
- 100% factory tested
- Full certified, Iridium approved, RoHS, CE, IEC60945

### **TECHNICAL SPECIFICATIONS**

IRIDIUM NETWORK			
9555 Handset	1616 - 1625 MHz		
Compressed Data		10 - 12 kbps	
Voice/Data Modulation		2.4 kbps	
POWER SPECIFICATIONS			
Power input voltage		9 - 32 V DC, 2A max	
AC Power Pack	90-250V AC 50-60Hz, Output 12V 45W		
Power Consumption (AMPS)			
Stand-by * - incl handset	45m/	0.5W	
Transmit - incl handset	0.5m/	A 6W	
Sleep Mode	18m	0.2W	
*When battery charged			
PHYSICAL SPECIFICATIONS	UNIT ONLY	PACKED	
Dimensions - mm	200 x 75 x 65	325 x 140 x 88	
Dimensions - inches	7.9 x 3.0 x 2.7	7.2 x 5.1 x 1.0	
Weight - kg	0.32	1.3	
Weight - lbs	0.7	2.86	
ENVIRONMENT SPECIFICATIONS			
Temperature	Degrees Cº	Degrees F°	
Operating Range	-30 to +70	-22 to +158	
Storage	-40 to +85	-40 to 185	
Humidity		< 93% RH	

CONNECTORS/INTERFA	CES			
Iridium - Antenna	Fixed Cable to TNC-Female			
GPS-Antenna	Fixed Cable to SMA-Female			
9-32V DC	4-way microFit (AC/DC adator, or DC lead)			
Privacy Handset Port	4 pole 3.5mm jack			
Data Port	USB Mini Base of Dock			
Bluetooth® Voice Only	In-built			
BUTTONS/LEDs				
Bluetooth®		Blue/Orange		
Mute/Ringer		Red		
Backlight		White LED		
Handset Release	Top of Cradle, No LED			
CERTIFICATIONS				
Iridium Approved		CE Compliance		
Electrical Safety		RoHS		
EMC Compliance		C Tick		
Independant Aeronautical certification MUST be gained prior installation				
KIT CONTENTS				
Beam IntelliDOCK Cradle				
Universal Mounting Bracket (RAM)				
9 - 32V DC Power Cable				
Quick Start Guide				
Quick Start Guide				

# **NETWORK ACCESS FEATURES**

- Global coverage pole to pole
- Low cost airtime rates
- Support all data services
- Support all Voice services

## ACCESSORIES

Beam Mast Antenna
Beam Whip Antenna
Magnetic Antenna
Bolt Mount Antenna
Bluetooth® Headset including car charger
Basic Privacy Handset
Antenna Cable 6m/18ft
Antenna Cable 12m/36ft

APPROVED BEAM RESELLER

www.beamcommunications.com



+61 3 8588 4500



+61 3 9560 9055



info@beamcommunications.com

AFRICA

ASIA

AUSTRALIA

EUROPE

MIDDLE EAST

NORTH AMERICA

SOUTH AMERICA